



ECVAV

SMART I/O™

DESCRIPTION

The Smart I/O™ ECVAV programmable variable air volume (VAV) controller is a state-of-the-art LonWorks™ controller with a factory integrated Direct-Coupled Actuator. On-board Airflow Sensor and motor control are complemented with an additional 9 channels of analog and digital I/O. The I/O is monitored and controlled by a Neuron 3150 chip with Free Topology communication over a LonWorks® network. The ECVAV can be utilized in many fixed and custom pressure-independent and pressure-dependent damper control applications.

The ECVAV sets a new standard in modular design to allow simple and easy replacement of the airflow pressure sensor, control circuit board and actuator assembly. The unprecedented, modular design provides for the lowest life cycle cost VAV controller in the industry. The ECVAV's removable terminal blocks further enhance its functional "real world" design.

The five universal inputs (UI) can be configured in a variety of ways. The controller can interface with resistive type sensors for temperature measurements. The UI's can measure voltage from humidity, CO₂ or other transducers. The UI's can input current for pressure measurements. The UI's can also be used to read digital inputs and dry contacts. With 12 bits of resolution, the universal inputs are field adaptable and accurate for many types of measurements.

An on-board regulated 20 VDC Power Terminal is available to operate current transducers for simplified interfacing and lower installed cost. The 20 VDC source is protected by an internal auto-reset fuse.

The four universal outputs (UO) can be configured as 24 VAC voltage sourcing Triac or 0-10 VDC outputs. The controller can use Triac outputs to provide on/off or pulsed control of valves, actuators, alarms, lights or other loads where the current does not exceed 1A at 24 VAC. The 0-10 VDC output has 10 bits of resolution for precision control of valves, actuators, and other external devices.

The ECVAV controller is protected from reverse power supply input wiring, over-voltages, transients, and other common events that can damage unprotected inputs and outputs.

The versatile and flexible I/O allows numerous VAV applications to be developed and implemented with the ECVAV.

User defined algorithms and functions can be programmed using VisualControl™, NodeBuilder, LonBuilder or other third party LONWORKS programming tools. The application program can be downloaded over the free topology network and is stored in non-volatile memory so it is retained even after loss of power.

The ECVAV assembly is field mounted to the VAV box damper shaft similar to the mounting of a standard actuator. Field wiring 18 to 22 AWG (2.0 to 0.34 mm²) passes through the conduit opening, connecting to the removable terminal blocks located under the snap-cover.

APPLICATIONS

- Pressure Independent
- Pressure Dependent
- Dual Duct
- Floating Control
- Up to 4-stages of Heat
- Modulating
- Room Pressure Control
- Energy Management
- Custom Applications

FEATURES

- LonTalk Protocol
- Free Topology Communication (FTT-10)
- Dedicated On-Board Airflow Sensor
- 5 Universal Inputs with 0-5V, 0-10V, 0-20mA, Thermistor or Dry Contact, Jumper Configurable
- Dedicated Damper Control, Floating Point Output
- 4 universal outputs with Triac or 0-10V, Jumper Configurable
- Field Proven, Rugged, Honeywell™ Actuator
- Modular Design, Lowest Life Cycle Cost
- Fully Programmable
- 2 Year Limited Warranty


SELECTION GUIDE

S-ECVAVP-F-

- └ B - 56K Flash Memory Only
- M- **STANDARD Selectable Memory (FLASH, SRAM)**
- C -Real Time Clock with Super Cap Back-up, Selectable Memory (Flash, SRAM) and 8K Serial EEPROM

SPECIFICATIONS

DIMENSIONS



CONTACT



SMART CONTROLS

Office:
10000 St. Clair Avenue
Fairview Heights, IL 62208
U.S.A.
Phone: 618-394-0300
Fax: 618-394-1575

E-mail:
sales@smartcontrols.com

Web site:
www.smartcontrols.com

Echelon, LONWORKS, 3150, NEURON AND LONTALK are trademarks or registered trademarks of Echelon Corporation.

Smart I/O is a trademark of Smart Controls, LLC. SMART CONTROLS, LLC reserves the right to make changes without further notice to this product for improvements in design and reliability. SMART CONTROLS, LLC does not assume any liability arising out of the application or use of this product; neither does it convey any license under its patent rights of others.

AGENCY



<u>General</u>		<u>Inputs</u>	
Communication:	LONTALK™ Protocol	Number:	5 Univ. plus dedicated airflow input
Transceiver:	FTT-10, Free Topology	Voltage:	0-5 Volts
Processor:	Neuron 3150 @ 20 MHz		0-10 Volts
Memory:	64K bytes FLASH	Current:	0-20 mA
	2K bytes SRAM (Neuron)	Thermistor:	Type 2, 3: 10Kohms (25°C, 77°F)
	0.5K bytes EEPROM (Neuron)	Digital:	Dry Contact
		Resolution:	12 bits
		Accuracy:	±1% FS (25°C, 77°F)
		Protection Circuitry:	Transient Over voltage, ESD
<u>Power</u>		<u>Outputs</u>	
Nominal Input Voltage:	24 VAC/DC	Number:	4 Univ. plus dedicated actuator outputs
Input Voltage Range:	21-28 VAC or 21-39 VDC	Digital:	Triac 1.0 A @ 24 VAC Internal Source
Typical Consumption:	4 VA	Voltage:	0-10 Volts
Maximum Consumption:	8 VA	Analog Output	
Output Power Protection:	+20V Output auto-reset fuse	Resolution:	10 bit
		Accuracy:	±1% FS (25°C, 77°F)
		Protection Circuitry:	ESD
<u>Environmental</u>		<u>Mechanical</u>	
Operating Temperature:	0 °C to +65.5 °C	Dimensions:	L 153 x W 92 x H 95 mm (6.02" x 3.62" x 3.74")
	32 °F to 150 °F	UL94-5V:	Meets Plenum Requirements
Storage Temperature:	-40 °C to +65.5 °C		
	-40 °F to 150 °F		
Relative Humidity:	5% to 95% (non-condensing)		
<u>Differential Pressure Sensor</u>		<u>Warranty</u>	
Range:	0-500 kPa (0-2"H ₂ O)	Period:	2 Years (Limited)
Accuracy:	±1% FS (25°C, 77°F)		
<u>Actuator</u>			
Motor:	Honeywell ML6161		
	Direct-Coupled		
Torque/Timing:	4 Nm (35 In. lb.)/90 sec.		
Angle of Rotation:	90 degree stroke		
Shaft Diameter Range:	10-13 mm (3/8-1/2")		

OPTION JUMPER SELECTIONS